

Utilization of Olive Waste Biochar for Sustainable Innovative Interlocking Blocks with Reduced Cement Content

Abdulmohsen AlFawaz, Abdulrahman Alammash, Abdulaziz Alghamdi, Omar Alghamdi, Abdulrahman Alshalwi, Ibraheem Aljerasi
Coach: Asad Hanif



Problem Statement

Cement production accounts for ~8% of global CO₂ emissions, while Saudi Arabia's Al-Jouf region generates large volumes of olive waste, creating disposal challenges. This project tackles both problems by converting olive pits into biochar through pyrolysis and using it to replace 10–30% of cement in interlocking blocks. The aim is to develop a sustainable, durable, and eco-friendly building material that reduces emissions, manages waste, and supports Saudi Vision 2030.

Constraints

- Reduce cement content by 10–15% in the mix.
- Operate pyrolysis reactor at 400–800°C.
- Ensure mold design achieves precise interlocking dimensions.

Specifications


- Furnace ramping rate: 5°C/min.
- Max block weight: 15 kg.
- Thermal conductivity: ≤1 W/m·K.
- Compressive strength: ≥18 MPa.
- Must pass durability test: W/C < 0.4
- Biochar yield from pyrolysis: ≥25%.

Prototype Design

- **Biochar Production (CHE):**
 - Pyrolyzed olive pits at 400-550°C; analyzed with XRF and TGA.
- **Concrete Mix (CEE):**
 - Designed mix with 10–30% biochar; tested for compressive strength.
- **Mold & Block Design (ME):**
 - Created 3D interlocking mold; fabricated using 3D printing.




Mix Design Samples for 50 mm Cubes			
Material	10% Biochar (g)	20% Biochar (g)	30% Biochar (g)
• Water	99.02	99.01	99.01
• Cement	297.02	263.99	213.38
• Biochar	32.99	66.00	94.73
• Sand	742.48	742.48	742.48
• Total	1171.51	1171.48	1149.60



Testing & Validations

• XRF and TGA for Biochar:



Spectrum: Map


El	AN	Series	unn. C [wt.%]	norm. C [wt.%]	Atom. C [at.%]	Compound	Comp. C [wt.%]	norm. Comp. C [wt.%]	Error (1 Sigma) [wt.%]
Si	14	K-series	0,75	5,10	5,03	SiO2	10,90	1,60	0,01
O	8		4,22	28,77	49,83		0,00	0,00	0,00
Cl	17	K-series	0,04	0,29	0,23		0,29	0,04	0,00
K	19	K-series	3,35	22,85	16,20	K2O	27,53	4,04	0,01
Ca	20	K-series	5,26	35,86	24,79	CaO	50,18	7,36	0,01
Cr	24	K-series	0,07	0,48	0,26	Cr2O3	0,71	0,10	0,00
Fe	26	K-series	0,68	4,61	2,29	Fe2O3	6,59	0,97	0,00
Zr	40	K-series	0,04	0,30	0,09		0,30	0,04	0,00
P	15	K-series	0,12	0,78	0,70	P2O5	1,80	0,26	0,00
S	16	K-series	0,05	0,31	0,27	SO3	0,77	0,11	0,00
Ti	22	K-series	0,05	0,33	0,19	TiO2	0,55	0,08	0,00
Mn	25	K-series	0,02	0,16	0,08	MnO	0,20	0,03	0,00
Sr	38	K-series	0,02	0,15	0,05	SrO	0,18	0,03	0,00
Rh	45	K-series	0,00	0,00	0,00		0,00	0,00	0,00
Total:			14,67	100,00	100,00				

• Average Compressive Strength:

- Mix Design with Biochar = **103.967 MPa**
- Mix Design without Biochar = **100.153 MPa**



• Finite Element Analysis (FEA):



Conclusion

This project successfully demonstrated the use of olive pit biochar as a partial cement replacement in interlocking blocks. Among the 10%, 20%, and 30% mixes tested, the 10% biochar mix was selected for its optimal balance of strength, durability, and sustainability. The final blocks met all key specifications and show strong potential as an eco-friendly material supporting Saudi Vision 2030.

Acknowledgment

We thank KFUPM for the support and resources provided. Special thanks to our coach, Dr. Asad Hanif, for his guidance, and to Dr. Amin Al Fakh (CEE), Dr. Mazen Nazal, and Ms. Najd Alhussain (ARC-EMS) for their support. We also appreciate the support of all departments involved.